



Digital Guardian

DG-PA-G3 Panic Button

Product Overview

The Digital Guardian range of panic button has been ergonomically designed and are ideal for use in commercial and domestic intruder installations.

All units are double push and are provided with integral resistors for use with most control panels. There is also the option for double pole connection if required. Spare terminals allow through connection for multiple units wired to one zone.

Available colour : White.



Features

- Silent operation
- Grade 3 Compliant
- Environmental class II
- FSL and D/P connection
- Multiple control panel and resistor options
- Easy connection of multiple units
- Cover and rear tamper
- Anti-lock reset mechanism
- Independent micro switch tamper
- Metal reset key
- Selectable normally closed or open contacts
- 1 year warranty

Approvals

CE Mark

RoHS Compliant

Technical Information

- Contact Voltage Rating : 30V dc
 Contact Current Rating : 1A (max)
 Operating temp. : -10°C to +40°C
 Operating Life : > 1 x 10⁸ Operations

The units comply fully with 'The ACPO 10 Point Plan' and all requirements under EN50131-1:2006 and PD6662:2010.

Ordering Information

| Available Colour | Dimensions W x L x H in mm |
|------------------|-------------------------------|
| White | 62 x 80 x 27 |

Mailing Address

VOSTOK Trading L.L.C,
304, 3rd Floor, Al Tawhidi Building,
Khaled Bin Waleed Road,
P.O. Box: 27106 - Dubai,
UNITED ARAB EMIRATES.

Contact Details

Tel: (+971 4) 3558816
Fax: (+971 4) 3558817
Email : sales1@digitalgardian.com /
sales2@digitalgardian.com /